

Eyewear and face protection

Glasses

Intensive & extreme use



Overglasses



Comfort & lightness



Classic & multi-purpose



Clear	Light mirror	Anti-mist N	Case
Yellow	Gradient	Anti-scratch K	Cord
Smoke	BB Blue blocker	Anti-mist	
P Polarised	T5 Welding	Anti-scratch	
Mirror	Lyviz	Antistatic	
		UV400	

Goggles

Panoramics



Compact



Accessories



Visors



Visor holders



Welding



Accessories



Innovation in comfort

Welding



2-in-1 interchangeable arms
 Innovative system that quickly transforms glasses with arms into goggles



Tilting arms
 Technology to adapt the glasses inclination to the shape of the face for a better hold



Double injection arms (D-fit)
 Co-injected TPE providing flexibility and solidity for optimal fit all day (reduces pressure points)



Adjustable arms length
 Allows you to adjust the glasses closer to the face for better fit all day



Nose bridge (D-PAD)
 Allows for a better fit for more comfort and stability



Detectable
 Addition of metal insert for magnetic or X-ray detection
 Ideal for the food industry

RECOMMENDED USE OF DIFFERENT GRADE NUMBERS FOR ARC WELDING ACCORDING TO STANDARDS EN169/EN175

Current Intensity (A)	Process							
	Coated Electrodes	MAG	TIG	MIG (heavy metals)	MIG (light metals)	Arc air gouging	Plasma cutting	Micro plasma welding
1.5								4
6								5
10			8					6
15	8	8						7
30				9			9	8
40			9		10	10		9
60								10
70	9	9	10					10
100	10	10					10	11
125				10				11
150	11	11	11				11	12
175					11	11		12
200								13
225	12	12	12					13
250				12				14
300		12	13		13	13		14
350	13							15
400				13				
450		13			14			
500	14							
600		14						

07/2022 - n°1759 - DOCGB1759 - GB - This is a non-contractual document subject to printing errors, reproduction is prohibited.

EYEWEAR AND FACE PROTECTION



Your safety at work

f @ y in
 www.deltaplus.eu

European standards

Visors

Choose the right shade

EN166

Applies to all types of individual protection of the eye which protects from hazards likely to damage the eye, except for nuclear radiation, x-rays, laser emissions and infrared emitted by low-temperature sources. Does not apply to eye protection for which separate standards exist (anti-laser eye protection, sunglasses for general use,...).

EN175

Specifications for the safety requirements for eye and face protection equipment for welding and related techniques (filters frames/ media).

EN169

Specifications of level numbers and requirements relating to the transmittance of filters to protect operators for welding and related techniques. Specification of requirements for welding filters with double number of levels..

EN170

Specifications of level numbers and of requirements relating to the transmittance of the filters for protection against ultraviolet radiation.

EN172

Specification of level numbers and requirements relating to the transmittance of filters for protection against solar radiation, industrial use.

EN379















Specification of the requirements for automatic welding filters, i.e. welding screens with automatic variation of the transmission factor. These screens are intended to protect operators during welding and related techniques.

EN1731

Material specifications, design, performance and test methods for eye and face mesh type protective, for professional use.

GS-ET 29

Requirements, performances, test methods relating to face shields providing protection against electric arcing.

	 VISOR H EN1731 / EN166	 VISOR HOLDER EN1731 / EN166	 VISOR HOLDER MINI EN1731 / EN166	 VISOR U EN166
 VISOR FLASH EN170 UV 2C-1.7 / EN166		 GS-ET 29 1FT 8-1-1 (CLASS 1)		 GS-ET 29 1FT 8-2-1 (CLASS 2) ASTM F2178 (14 CAL/CM²)
 VISOR TORIC EN170 UV 2C-1.2 / EN166	 1 AT 389	 1 AT 389		 1 AT 389
 VISOR TORIC T5 EN169 5 / EN166	 1 AT 39	 1 AT 39		 1 AT 39
 VISORPC EN166	 BALB12 EN166 1 BT 3	 1 BT 3	 1 BT 3	
 VISORG EN1731 F	 PICO2 EN1731 F/F	 F	 F	

Yellow



Increases contrasts and gives a feeling of depth. Suitable for night driving.

Smoke



Very good protection against the risk of natural glare with good color recognition.

Mirror / Light Mirror



Reflect light from the surface. Particularly suitable for activities carried out in intense light.

Blue Blocker



Lens filtering 65% of blue light.

Polarised



High risk of dazzling and work on reflective surfaces. Eliminates reverberation, improves color perception and provides optimal visual comfort.

Gradient



Darker gradient at the top of the lens becoming lighter towards the bottom. The upper part protects from the intensity of the light. The lower part offers excellent vision.

Clear



Protects against mechanical hazards without glare.


LYVIZ™



LYVIZ treated lenses have a very strong resistance to scratches and greatly limit the formation of fogging on the internal and external face and this permanently.



The drops of water (or other liquid) bead on the glasses, do not stain



Fingerprints and other greasy marks do not mark.